

HONUL, Melania; ZASADZIEN, Zdzislaw

Shelter box for sedimentation jars for measurements of dust
contamination of the air. Roczn panstw zakl hig 14 no.1:27-30
'63.

1. Voivodeship Sanitary and Epldemiological Station, Opole.

MAJEWSKI, Janusz; ZASADZIEN, Edzislaw; PYSZ, Jozef

Smallpox in the Opole Province in 1963. Przegl. epidem. 18
no.2:197-204 '64.

1. Z Wydzialu Zdrowia i Opieki Spolecznej Prezydium Wojewodzkiej
Rady Narodowej w Opolu i z Wojewodzkiej Stacji Sanitarno-
Epidemiologicznej.

WANTUCHOWSKI, Jerai; ZASADZENSKI, J.

Conditions for producing rolled aluminum cables by means of
the Properzi process at the Skawina Aluminum Plant. Koh lap
96 no.12:534-538 D '63.

1. Banayaszati es Kohaszati Akademia, Krakow.

ZASANSKIY, V.V.

Achievements of innovators should be available to all workers.
Mashinostroitel' no.7#10-11 JI '64. (MIRA 17:8)

110197-66 EWP(a)/EWP(t)/EWP(b) LJP(c) JD

ACC NR: AP5028456

SOURCE CODE: UR/0286/65/000/0:0/0019/0019

AUTHORS: ⁵⁵Minovich, M. A.; ⁵⁵Shoyerson, A. L.; ⁵⁵Filippova, Zh. M.; ⁵⁵Atroshechenko, V.

⁵⁵Zaachin, A. P.; ⁵⁵Ivanovskiy, P. P.

ORG: none

TITLE: Method for obtaining nitric acid. ²⁷⁵Class 12, No. 175492 [announced by ⁵⁵State Scientific Research and Design Institute for the Nitrogen Industry and Products of azotnoy promyshlennosti i produktov organicheskogo sinteza)]

SOURCE: Byulleten' izobreteniy i tovarnykh znakov, no. 20, 1965, 19

TOPIC TAGS: nitric acid, nitrogen oxide, nitrogen compound

ABSTRACT: This Author Certificate presents a method for obtaining nitric acid at a pressure of 4-7 atm by absorbing gaseous nitrogen oxides in water in an absorption tray-type column. To obtain 68--80% nitric acid, liquid oxides of nitrogen are introduced into the column at a point below the formation of 50--63% nitric acid. The reaction may also be carried out by introducing air into the column at a point below which the liquid oxides of nitrogen are introduced.

SUB CODE: 11/ SUBM DATE: 18Oct63/

Card 1/1

UDC: 661.56

ZASHCHEPIN, A.N., kand. tekhn. nauk; CHERNIGOV, V.A., kand. tekhn. nauk

Vibration as an effective method for mixing concrete mixes. Avt.
dor. 24 no.2:12-13 P '61. (MIRA 14:3)
(Vibrators) (Mixing machinery) !

SOV/79-29-10-48/60

AUTHORS: Korshak, V. V., Mozgova, K. K.,
Zasechkina, A. P.

TITLE: The Influence of Low-Molecular Compounds on the Photo-
chemical Destruction of Polyethylene Terephthalate (Vliyaniye
nizkomolekulyarnykh veshchestv na fotokhimicheskuyu
destruktsiyu polietilentereftalata)

PERIODICAL: Zhurnal obshchey khimii, 1958, Vol 28, Nr 10,
pp 2847 - 2853 (USSR)

ABSTRACT: In the paper under discussion, the conversion process
of polyethylene terephthalate (Lavan) under the
influence of the full irradiation by a lamp PTK,-2
on this polyester, as well as of the closer spectral
region within the limits of 300-320 m μ , was investigated.
At the same time, an attempt was made to determine the
influence of certain low-molecular compounds of various
structures on the conversion process of polyethylene
phthalate on full ultraviolet irradiation. The samples
of this compound available to the authors did not
yield fully uniform absorption spectra; they differed
from those already published, due, probably, to the

Card 1/2

The Influence of Low-Molecular Compounds on the Photo-chemical Destruction of Polyethylene Terephthalate SOV/79-2840-48/60

difference in the composition of the polyester (Ref 6). The absorption spectra of the compounds enumerated are listed in the preceding report (Ref 7). The changes in the properties of the irradiated foils were determined from the changes in molecular weights, mechanical properties, and spectral characteristics. It was found that the decomposition of polyethylene terephthalate on full ultraviolet irradiation by the above mentioned lamp occurs far more intensively than on irradiation at a wave length of 300-320 m μ . The addition of low-molecular organic compounds to the polyethylene terephthalate affects its decomposition process. The results obtained harmonize with those arrived at under identical conditions on the decomposition of polystyrene. There are 6 figures, 1 table, and 8 references, 2 of which are Soviet.

SUBMITTED: August 5, 1957
Card 2/2

KORSHAK, V.V.; MOZGOVA, K.K.; SHKOLINA, M.A.; Prinimali uchastiye:
ZASECHKINA, A.P.; VOLKOVA, A.I.

Preparation of graft copolymers. Part 8. Vysokom.sped. 3 no.11:
1655-1660 N '61. (MIRA 14:11)

1. Institut elementoorganicheskikh soyedineniy AN SSSR.
(Nylon) (Styrene)

NORSHAK, V.V.; MOZGOVA, K.K.; SHKOLINA, M.A.; NAGDASOVA, I.P.;
BERESTNEV, V.A.; Prinsipalni uchastiyete: YEGOROVA, Yu.V.;
ZASECHKINA, A.P.; VOLKOVA, A.I.; SAZONKINA, M.T.

Preparation of graft copolymers. Part 12. Vysokom.sped. 5
no.2:171-175 F '63. (MIRA 16:2)

1. Institut elementoorganicheskikh soyedineniya AN SSSR.
(Polymers)

ZASECHKINA, A. P.

4419
S/190/62/004/010/002/010
B144/B186

15 90-0

AUTHORS: Korshak, V. V., Mozgova, K. K., Shkolina, M. A.,
Korostylev, B. M., Linovetskaya, O. Ya., Zasechkina, A. P.

TITLE: Synthesis of graft copolymers

PERIODICAL: Vysokomolekulyarnyye soyedineniya, v. 4, no. 10, 1962,
1469-1473

TEXT: The copolymerization of polyethylene terephthalates (I) ("Lapsan",
Mostaphan, Gronar) with monomers and monomer mixtures was studied in an
attempt to increase the adhesiveness between (I) and the photographic
emulsion layer containing gelatin. After a heat treatment of no more
than 10 min at 90 - 120°C, the samples were kept immersed in the
monomer or monomer mixture for 7 - 64.5 hrs at 40 - 80°C. 2-methyl-5-
vinyl pyridine, vinyl pyrrolidone, and methyl methacrylate (II) were used
singly or in mixtures with acrylonitrile, methacrylic acid (III), epoxy
resin, styrene, carbinol cement, and gelatin dissolved in acrylic acid
(IV). After treatment with solvents such as benzene or water, and
dissociation, the adhesiveness was examined by way of the 5-ball system.
*Card 1/2

Synthesis of graft copolymers

5/190/62/004/010/003/010
B144/B186

The tensile strength of 8 · 10 mm specimens was tested with a Schopper dynamometer at an elongation rate of 10 cm/min. Laysan, Hostaphan, and Cronar behaved similarly. The best adhesiveness was reached by copolymerizing (I) with (II-III) mixtures independently of their mixing ratio, and with (IV) in thin monomer layers (2 - 5 μ by weight). The viscosity could not be tested, as (I) after grafting, was no longer soluble in xylene. Grafting reduced the elongation at rupture, whilst slightly increasing the tensile strength, but did not affect the optical properties and orientation. There are 1 figure and 4 tables.

ASSOCIATION: Institut elementoorganicheskikh soyedineniy AN SSSR
(Institute of Elemental Organic Compounds AS USSR).

SUBMITTED: May 20, 1961

Card 2/2

ZASEDA, Igor'[Zasieda, Ihor], master sports

White heart of the Pamir. Znan. ta pratsia no,2:21-22 F '63.
(MIRA 16:4)

(Pamirs--Mountaineering)

ZASEDATELEV, A.M., kand.tekhn.nauk; RUKHADZE, V.A., inzh.

Relationship between the rigidity of bellow-type transmitters
and the static pressure. Nauch.dokl.vys.shkol'y; mash.i prib.
no.1:228-235 '58. (MIRA 12:1)

1. Predstavleno kafedroy "Pribory tochnoy mekhaniki" Moskovsko-
go vysshego tekhnicheskogo uchilishcha imeni N.E. Baumana.
(Measuring instruments)

RYABINKIN, V.P., inzh.; ZASEDATELEV, G.F., inzh.

Mechanizing processes of welding sections of the super-
structure on diesel-powered loose-cargo ships. Sudostroenie
25 no.9:47-54 9 '59. (MIRA 12:12)
(Ships--Welding)

ZASIDATELEV, I., polkovnik

Zeroing in mortars with the aid of a range finder and
a stop watch. Voen. vest. 39 no.6:66-70. Je. '59. (MIRA 12:9)

(Mortars (Ordnance)) (Range finding)

ZASENATELEV, I., gvardii polkovnik; KONOVALOV, N., polkovnik.

Mortar marksmanship training. Voen.vest. 36 no.4:26-31 Ap 1967
(MLBA 9:8)

(Mortars (Ordnance))

ZASEDATELEV, I., gvardii polkovnik.

Position area survey of a mortar battery on the basis of its
fire. Voen.vest. 36 no.8:61-65 Ag '56. (MLBA 9:10)

(Artillery drill and tactics)

ZASDA MELEV, I., gvardii polkovnik.

Review and analysis of firing the 82-mm mortar. Voen. vest. 35 no.5:
71-73 My '55. (MIRA 9:7)
(Mortars (Ordnance)) (Russia--Army--Artillery)

GORYAINOV, K.E., doktor tekhn.nauk; ZASEDATELEV, I.B., kand.tekhn.nauk

Vacuum cooling of large gas-concrete wall blocks. *Biul.tekh.inform.*
4 no.11:21-22 N '58. (MIRA. 11:12)

(Autoclaves) (Concrete blocks)

GORYAZHOV K.E., doktor tekhn.nauk; ZASEDATEL'NY, I.B., kand.tekhn.nauk

Thermophysical processes during the autoclave hardening of large porous
concrete products. Bet. 1 shel.-bet. no.2:62-67 F '59.
(MIRA 12:3)

(Lightweight concrete) (Autoclaving)

PANIN, A.S., kand.tekhn.nauk; ZASEDATELEV, I.B., kand.tokhn.nauk

Manufacturing ash gravel. Stroim.at. 8 no.1:14-17 Ja '62.

(MIRA 15:5)

(Gravel)

ZHUKOV, Dmitriy Vasil'yevich, kand. tekhn. nauk; ZASEDATELEV, Igor'
~~Borisovich, kand. tekhn. nauk; PALEVSKIY, S.A., nauchnyy red.;~~
SHIROKOVA, G.M., red. izd-va; NAUMOVA, G.D., tekhn. red.

[Heating and drying of buildings and industrial structures
erected in the winter] Obogrev i sushka zdaniy i promyshlen-
nykh sooruzheniy, vozvodimykh v zimnikh usloviyakh. Moskva,
Gosstroizdat, 1962. 154 p. (MIRA 15:8)
(Heating) (Drying apparatus)

ZHUKOV, D.V., kand.tekhn.nauk; ZASEDATELEV, I.B.

Electric heating of reinforced concrete floors in building under winter
conditions. Prom.stroi. 37 no.8:47-49 Ag '59. (MIRA 12:11)
(Electric heating) (Floors)

SOV/19-58-6-633/685

AUTHORS: Goryaynov, K.E., Zasedatelev, I.B., Avrutin, M.L.,
Volchek, I.Z., and Lizogub, A.L.

TITLE: A Method of Producing Concrete, Silicate and Other
Products (Sposob izgotovleniya betonnykh, silikat-
nykh i drugikh izdeliy)

PERIODICAL: Byulleten' izobreteniy, 1958, Nr 6, p 140 (USSR)

ABSTRACT: Class 80a, 9¹⁰. Nr 113746 (587315 of 2 Dec 1957).
Submitted to the Committee for Inventions and Dis-
coveries at the Ministers Council of USSR. Produc-
ing concrete, silicate and similar products in
autoclaves by steaming under pressure, and prevent-
ing detrimental temperature stresses from appearing
in the products as well as speeding up the work
process by producing a vacuum in the autoclave
after the process.

Card 1/1

GORYAYNOV, K.E., doktor tekhn. nauk; ZASEDATELEV, I.B., kand.tekhn.nauk

Using vacuum techniques for cooling large porous products in autoclaves. Stroi. mat. 6 no.6:18-20 Je '60. (MIRA 13:6)
(Autoclaves) (Lightweight concrete)

ZASEDATELEV, I.B.

GORYAYNOV, K.E., doktor tekhn.nauk; VOLCHER, I.Z., kand.tekhn.nauk;
ZASEDATELEV, I.B., inzh.

Using lightweight cinder concrete in making large wall blocks. Pat.
i zhel.-bet. no.6:229 Ja '58. (MIRA 11:6)
(Cinder blocks)

ZASEDATELEV, I.B.

GOREYAYNOV, K.H., doktor tekhn. nauk; YEFIMOV, A.D.; VOLCHEK, I.Z., kand.
tekhn. nauk; AVRUTIN, M.L., inzh.; LIZOGUB, A.A., inzh.;
ZASEDATELEV, I.B., inzh.

Large wall blocks made of autoclave hardened lightweight concrete.
Biul. tekhn. inform. 4 no.2:1-5 P '58. (MIRA 11:3)

1. Chlen-korrespondent Akademii stroitel'stva arkhitektury (for
Yefimov).

(Concrete blocks) (Lightweight concrete)

ZASKDATELEV, I.B., inzhener.

Evaluation of heat processes in the accelerated hardening of
concrete. Biul.tekh.inform. 3 no.6:17-20 Je '57. (MIRA 10:10)
(Concrete)

~~ZASEDATSEV, I.B.~~

ZHUKOV, D.V., kand.tekhn.nauk; ZASEDATSEV, I.B., inzhener.

Shortcomings in the operation of steam chambers and methods of
eliminating them. Stroi.prom. 35 no.7:7-9 J1 57. (MIRA 10:10)
(Autoclaves)

^S
ZAKHEDATELEV, I.B., Cand Tech Sci--(diss) "Study of thermo-physical
process ~~of~~ ^{as during the} hardening of concrete in ~~the~~ periodic action chambers."
Mos, 1958. 15 pp (Mos Inst of Engineers of Mining Construction of
^(Moscow City Executive Committee)
the ~~Moscow Institute~~, (KL, 25-58, 113)

- 99 -

GORIYAYNOV, K.E., doktor tekhn.nauk; YEFIMOV, A.D.; VOLCHEK, I.Z.; AVRUTIN, M.L.; ZASEDATELEV, I.B.; HECHAYEV, G.A., red.izd-va; PUL'KINA, Ye.A., tekhn.rsd.

[Large aerated-cement wall blocks; practices of the Main Administration for Housing and Public Construction in the city of Leningrad] Krupnye gazobetonnye stenovye bloki; iz opyta Glavleningradstroia. Pod red. K.E.Goriainova. Leningrad, Gos.izd-vo lit-ry po stroit., arkhit. i stroit. materialam, 1959. 102 p. (MIRA 13:1)
(Leningrad--Building blocks) (Lightweight concrete)

AVETIKOV, V.G., kand.tekhn.nauk; ZIN'KO, E.I., kand.tekhn.nauk; ZASEDATELEVA,
~~MIRA~~ inzh.; LESNIKOVA, L.A., inzh.

Steatite with an expanded temperature range of vitrification. Trudy
GIEKI no.4:34-46 '60. (MIRA 15:1)
(Ceramics) (Electric insulators and insulation)

MASIDATELEV, S. M. (NIITeplopribor, Moscow)

"Investigation and Construction of a New Type of Apparatus with a Force Compensation by Pressurized Air."

Report presented at the Scientific Seminar on Pneumo-Hydraulic Automation, 28-29 May 1957, at the Inst. for Automation and Remote Control (Iat), Acad. Sci. USSR

Avtomatika i Telemekhanika, 1957, vol. 18, No. 12, pp. 1148-1150, (author SEMIKOVA, A. I.)

ZASEDATELEV, S.M., inzhener.

Coiling of springs retaining stresses between the coils. [Trudy] MVTU no.
16:90-95 '52. (MLRA 6:6)
(Springs (Mechanism))

ZASDATELEV, S.M., inzhener.

Graphic method in the solution of some problems in elastic-plastic bending of bars in large-scale transposition. [Trudy] MTU no. 26:173-184 (MLRA 7:5)

'53.

(Flexure--Graphic methods) (Elastic rods and wires)

ZASRD:TELEV, S. M.

ZASRD:TELEV, S. M. "Spiral Springs with Initial Tension and Their Design." Min of
Higher Education USSR, Moscow Order of Labor Red Banner Higher Technical School imeni
Bauman, Moscow, 1955 (Dissertations For Degree of Candidate of Technical Sciences)

SO: Knizhnaya Letopis' No. 26, June 1955, Moscow

ZASEDATELEV, S.M.

ANDEEYEV, L.Ye., kandidat tekhnicheskikh nauk; BIDESMAN, V.L., kandidat tekhnicheskikh nauk; BOYARSHINOV, S.V., kandidat tekhnicheskikh nauk; VOL'MIR, A.S., doktor tekhnicheskikh nauk; DIMENBEIG, Y.M., kandidat tekhnicheskikh nauk; ZASEDATELEV, S.M., inzhener; KINASHOVILI, R.S., doktor tekhnicheskikh nauk, professor; KOVALENKO, A.D.; MARUSHIN, V.M., kandidat tekhnicheskikh nauk; MALININ, N.N., kandidat tekhnicheskikh nauk; PONOMAREV, S.D., doktor tekhnicheskikh nauk; PRIGOROVSKIY, N.I., doktor tekhnicheskikh nauk; TETEL'BAUM, I.M., kandidat tekhnicheskikh nauk; UMANSKIY, A.A., doktor tekhnicheskikh nauk, professor; FEDOS'YEV, V.I., doktor tekhnicheskikh nauk; SERENSEN, S.V., redaktor; TRAPEZIN, I.I., kandidat tekhnicheskikh nauk, redaktor; KARGANOV, V.G., inzhener, redaktor; SOKOLOVA, T.F., tekhnicheskiy redaktor.

[Mechanical engineer's manual; in 6 volumes] Spravochnik mashinostroiteliya; v shesti tomakh. Izd.2-e, ispr. i'dop. Moskva, Gos. nauchno-tekhn.izd-vo mashinostroit. lit-ry, Vol.3, 1955. 563 p. (MLRA 8:12)
(Mechanical engineering)

ZASDATHLEV, S.M.

Coiling springs with initial stresses. [Trudy] MVTU no.31:109-119
'55. (MIRA 8:5)
(Springs (Mechanism))

ZASEDALEEV, S.M.

Loss of resilience in tension coil springs. [Trudy] MVTU no.31:120-
125 '55. (MIRA 8:5)
(Springs (Mechanism))

MASEDATELEV, S.M., inshener.

Helical springs with initial tension and their calculation. [Trudy]
MVTU no. 46:71-86 '55. (MIRA 9:4)
(Springs (Mechanism))

RABINOVICH, Lev Vladimirovich; ZASEDATELEV, S.M., ed.

[Phase-plane methods in the theory and practice of relay-type servo systems] Metody fazovoi ploskosti v teorii i praktike releinykh slediaschikh sistem. Moskva, Energiia, 1965. 150 p. (Biblioteka po avtomatike, no.143)

(MIRA 18:8)

ZASEDATELEV, S.M.

18

PHASE I BOOK EXPLOITATION SOV/5519

Kremlevskiy, P. P., Candidate of Technical Sciences, ed.

Teplotenergeticheskiye i khimiko-tekhnologicheskiye pribory i regulatory (Instruments and Regulators in Heat-Power and Chemical Engineering) Moscow, Mashgiz, 1961. 307 p. Errata slip inserted. 8,500 copies printed.

Ed. of Publishing House: G. A. Dudusova; Tech. Ed.: L. V. Shchetina; Managing Ed. for Literature on the Design and Operation of Machines. Leningrad Department, Mashgiz; F. I. Fetisov, Engineer.

PURPOSE: This book is intended for engineers and technicians who construct, design, and operate industrial instruments and regulators.

COVERAGE: The book deals with new investigations in the field of automatic checking and regulation of heat-power and chemical industrial processes. The following problems are discussed: improvement of two-position

control operation; effect of mass action and damping on proportional control; new proportional plus integral and programming electronic regulation systems; complete automation of open-hearth furnaces; automation of boilers with variable load capacity; measurement of pulsating flow; measurement of dust flow; ultrasonic and magnetic induction flowmeters; pneumatic compensating differential manometers; aggressive-fluid flowmeters; new magnetic and optical-acoustic gas analyzers; concentration meters; and chlorine and coagulant regulators. The book is the fifth in a series containing reports on the investigations carried out by the Section on Heat-Engineering Control Instrumentation and Automation of the Leningradskoye otdel'noye Nauchno-tekhnicheskoye obshchestvo prihorostroyeniya promyshlennosti (Leningrad Branch of the Scientific and Technical Society of the Instrument-Building Industry.) All the articles presented in this book were discussed either at sessions of the above section or at the conference on measurements of mechanical quantities called by the section, the VNIM (Vsesoyuzny nauchno-issledovatel'skiy institut metrologii) im. D. I. Mendeleeva -- All-Union Scientific Research Institute of Metrology (now D. I. Mendeleev), and the Leningradskiy dom Metrologiy (now A. M. Gor'togo (Leningrad Home for Scientists Imeni A. M. Gor'kogo)). No personalities are mentioned. There are 65 references: 41 Soviet, 20 English, and 4 German. References accompany most chapters.

TABLE OF CONTENTS:

Foreword

PART I. AUTOMATIC CONTROL OF INDUSTRIAL PROCESSES

Ch. I. Kampe-Neman, A. A. Two-Position Automatic Control and Methods of Improving Its Properties	5
1. Methods of improving properties of two-position control without changing the block diagram of the system	5
2. Discontinuous two-position control	8
3. Introduction of additional pulses to the rule of regulating according to the 1st and 2d derivatives (three-position control)	10
4. Increasing the number of inflow stages (three-position control)	13
5. Application of exponential feedbacks (two-position static and two-position proportional plus integral control)	14
Ch. II. Kats, A. M., and N. F. Gonok. Investigation of Proportional Control, Taking into Account the Mass of the Sensitive Element and Damping in the System Unit	23
1. Equations for a control system with variable speed of the servomotor and inertia of the sensitive element	24

Cont'd on p.

18

SOV/SN19			
Instruments and Regulators (Cont.)			
2.	Limit of system stability		28
3.	Formation of transients		32
4.	Equations for a control system with pure time delay		36
Ch. III. Strashun, A. Z. Automatic Regulators			42
1.	Basic types of regulators		42
2.	RU4-01 and RU4-06 regulators		44
3.	RU4-15 regulator		49
4.	RU4-16A regulator		51
5.	RU5-01 and RU3-02 programming devices		54
Ch. IV. Dembovskiy, V. Y., and S. V. Yurovskiy. Complex Automation of Open-Hearth Furnaces			56
1.	Programming elements of the circuit		58
2.	Automatic correction of the programming of the thermal operating conditions		61
3.	Automatic regulation of flame angle		63
4.	Regulation of fuel oil consumption		64
5.	Correction of fuel oil consumption by the frequency of throwing over the valves		66
Ch. V. Shifrin, M. Sh. Building Up Control Circuits for Shipboard Boiler Systems			68
1.	Regulation of boiler water-supply system		72
2.	Regulation of combustion process in the boilers		73
3.	Regulation of air and steam pressure		76
PART II. FLOW RATE MEASUREMENT			
Ch. VI. Kremlevskiy, F. F. Criterion of Pulsating-Flow Damping			78
Ch. VII. Shatil', A. A. Application of Narrowing Devices for Measuring Dust Flow in a Pneumatic Traffic System			80
Ch. VIII. Kholmunin, A. S. Ultrasonic Flowmeters			101
1.	Phase method		101
2.	Pulse-time method		110
Ch. IX. Zasodimskiy, S. M., V. A. Rubtsov, and K. A. Savel'. <u>Automatic Compensating Differential Manometers</u>			115
1.	Errors in compensating differential manometers		116
2.	Means for increasing operating reliability of membrane differential manometers		124
3.	Differential manometers with pneumatic power compensation		128
Ch. X. Niblitin, B. I., I. D. Velt', and V. K. Rukavishnikova. <u>RI-Type Induction Electromagnetic Flowmeters</u>			134
Ch. XI. Bushinsky, N. I. <u>Tachometric Vase-Type Flowmeters for Salpetric Acid</u>			141
1.	Measuring average flows		143
2.	Measuring high flows		146
3.	Measuring low flows		150
Ch. XII. Mikhaylov, B. F. <u>Measuring the Flow of Aggressive Liquids</u>			151
1.	Inductive flowmeter for registration of quick-changing liquid flows		151
2.	Tachometric vase-type liquid flowmeters		154
3.	Measurement of extremely low flows		156
PART III. MEASUREMENT OF THE CONCENTRATION OF INDIVIDUAL COMPONENTS IN GASES AND LIQUIDS			

ZASHEDELEV, S.M. (Moskva); RUKHADZE, V.A. (Moskva)

Design of force-balanced transmitters. Avtom. i telex. 21
no.6:918-928 Ja '60. (MIRA 13:7)
(Transducers)

2 ASE DATE L E U S M

28(1) PHLASE I BOOK ~~XXXXXXXXXX~~ SOV/2702

Akademiya nauk SSSR. Institut avtomatiki i telemekhaniki. Seminar po pnevmogidravlicheskoy avtomatike. Ist. Moscow, 1957. Sistyemy, ustroystva i elementy pnevmo- i gidromekhaniki (Gornaliv) (Pneumatic and Hydraulic Circuits, Devices, and Elements in Automation) (Collection of Papers) Moscow, Izd-vo AN SSSR, 1959. 233 p. Errata slip inserted. 2,700 copies printed.

Bezer, Ed.: M. A. Ayterman, Doctor of Technical Sciences, Professor. Ed. of Publishing House: A. A. Tal. Tech. Ed.: I. P. Polyakov.

PURPOSE: This collection of papers is intended for scientific research workers and engineers in the field of design and construction of pneumatic and hydraulic equipment and accessories for automation.

COVERAGE: This collection contains papers read at the Seminar on Pneumatic and Hydraulic Devices for Automation, May 28, 1957. The collection is divided into the following three groups: 1) newly developed pneumatic and hydraulic circuits; 2) pneumatic and hydraulic devices, including regulating units, transmitters and transducers, actuating mechanisms, special-purpose devices, and auxiliary equipment; and 3) elements of pneumatic and hydraulic devices for automation, such as controlled and permanent nozzles and diaphragms. No particularities are mentioned. References follow several of the papers.

Podgornitskiy, N. L., and E. M. Braverman. Assocoy. KIRMA Three-Component Regulating Unit. 50

Pravobratnyy, V. M. Assocoy. Small-size Hydraulic Regulating Unit. 57

TAI AN SSB

Zaslavskiy, S. M., and V. A. Bukhadze. Assocoy. Problems in Constructing Primary Instruments -- Differential Pressure Transmitters With Pneumatic Force Compensation. 61

This paper is a theoretical discussion of differential transmitters dealing with their sensitivity, errors, and reliability.

Krasnitskiy, Yu. V. Assocoy. Electropneumatic Transducers. IAC AN SSSR. 77

~~XXXXXXXXXX~~ V. M. Assocoy. Static Characteristics of a Pneumatic Relay With Constant Pressure Drop in Nozzles. 86

This paper discusses the static characteristics of a back-pressure pneumatic relay with indicators that are not sensitive to minute gap changes.

Zasodetev, S. M., and V. A. Bukhadze. Assocoy. Differential Pressure Transmitters With Pneumatic Force Compensation (Review of Non-Soviet Designs). 91

Tamir, V. P. Assocoy. General-purpose Hydraulic Power Servo-drive. 99

Arkhangel'skiy, A. F. Hydraulic Universal Variable-speed Transmission (URS). 103

This paper describes an axial-piston variable-speed transmission. Its technical specifications and fields of application are discussed.

Belushkin, S. A. Assocoy. Equations for a Stabilizing System With a Hydraulic Actuator Connected With a Control Device by Hydraulic Main Lines. 112

Equations of the motion of the actuator piston and elements of the control device are given. Design examples are presented.

SOV/124-58-10-11826

Translation from: Referativnyy zhurnal, Mekhanika, 1958, Nr 10, p 151 (USSR)

AUTHOR: Zasedatelev, S.M.

TITLE: Computation of Extension Springs Wound With an Initial Tension (Compression of Loops) [Raschet pruzhin rastyazheniya, navitykh s nachal'nym natyazheniyem (mezhvitkovym davleniyem)]

PERIODICAL: V sb.: Vopr. proyektir., izgotovleniya i sluzhby pruzhin. Moscow--Leningrad, Mashgiz, 1956, pp 59-85

ABSTRACT: Various possibilities of application of springs with compressed loops in machines and instruments are examined. Critique of the existing arbitrary recommendations on prestressing of springs is given, and a method, derived by the author, permitting selection of the degree of prestressing in accordance with conditions of stability, is presented. Deformations which occur in the wire during winding operations and which ensure a residual torque are analyzed by considering the successive stages in the manufacture of springs. The magnitude of the initial tensile stress is computed on the basis of the mechanical properties of the material in accordance with the theory on small elastic-plastic deformations

Card 1/2

SOV/124-58-10-11826

Computation of Extension Springs Wound With an Initial Tension

as applied to bending and twisting of a round rod. The computation of the design strength of the springs is based upon torsional stresses and the corresponding yield point. Investigations were also performed in order to determine how the initial nonlinear portion of the stress-strain curve of a spring is affected by such factors as deformation of end loops, variation in loop-compression stresses between individual loops, and deviation of the line of action of the load from the geometrical axis of the spring.

V. A. Bykov

Card 2/2

ZASEDATELEV, V.N., inzhener.

Industrializing and mechanizing gas line construction. Gor.khoz.
Mosk. 24 no.2:1-8 F '50. (MLRA 7:11)
(Moscow--Gas pipes) (Gas pipes--Moscow)

ZASEDATELEVA, G.S., kand.veterinarnykh nauk

Methods of selecting brucellar animals before they are vaccinated in fresh infection foci and the epizootiological importance of cows which react long after the vaccination. Trudy VIEV 26:98-101 '62. (MIRA 16#2)

1. Laboratoriya po izucheniyu brutselleza Vsesoyuznogo instituta eksperimental'noy veterinarii.
(Brucellosis in cattle)

MORYAKOVA, O.I., kand.veterinarnykh nauk; ZASEDATELEVA, G.S., kand.
veterinarnykh nauk

Study of immunobiological reactions in cattle vaccinated with
strain no.19 under different epizootiological conditions. Trudy
VIEV 26:90-97 '62. (MIRA 16:2)

1. laboratoriya po izucheniyu brutselleza. Vsesoyuznogo instituta
eksperimental'noy veterinarii.
(Brucellosis in cattle) (Immunology)

ACC NR: AP6030796 (A,N) SOURCE CODE: UR/0346/66/000/009/0015/0018

6

AUTHOR: Vershilova, P. A.; Ivanov, M. M.; Orlov, Ye. S.; Kaymazova, Ye. I.;
Kurdina, D. S.; Zagdataleva, G. S.; Mikhaylov, N. A.; Pinigin, A. P.; Merinov,
S. P.; Dranovskaya, Ye. A.; Davydov, N. N.

ORG: none

TITLE: Brucellosis cultures isolated from deer in the northern Soviet Union

SOURCE: Veterinariya, no. 9, 1966, 15-18

TOPIC TAGS: brucellosis, brucella culture, disease vector, deer, animal disease

ABSTRACT: Brucellosis is widely distributed among deer in the northern part of the Soviet Union. In general they serve as carriers and epizootic reservoirs of brucellosis in cattle and sheep. The most typical species is *Brucella abortus*, with the other two common types rare or absent. A fourth type, *Br. rangifer*, differing from the others, was also isolated.

[WA-50; CSR No. 12]

SUB CODE: 06/ SUBM DATE: none/ ORIG REF: 014/ OTH REF: 010

Card 1/1

UDC: 619:616.981.42-02:636 294

15

ca

Treating coal and cellulose with ammonia under pressure and heating. S. S. Dragunov and A. N. Zagladina. *Trans. Sci. Inst. Fertilizers (Soviet Union)* (U.S.S.R.) No. 127, 53-61 (1961).—Brown coal, peat and cellulose treated with liquid and gaseous ammonia and $(NH_4)_2CO_3$ in an autoclave at various pressures, temps. and time intervals proved the following: the brown coal without extra pressure combines with NH_3 in quantities slightly higher than the no. of carboxyl groups in it. At higher pressures the quantity of NH_3 equal to the phenol hydroxyl and carboxyl groups. Coal of amorphinite origin combines with very little NH_3 . Cellulose takes up more NH_3 at higher temp. and in the presence of O. As much as 30% N could be combined with the cellulose. If ammoniated cellulose is acidified with Cl or HNO_3 , the product becomes easily sol.

J. S. Joffe

ASS. S. A. METALLURGICAL LITERATURE CLASSIFICATION		INDEXING	
GROUP	SUBGROUP	CLASSIFICATION	INDEXING
1	1	1	1
2	2	2	2
3	3	3	3
4	4	4	4
5	5	5	5
6	6	6	6
7	7	7	7
8	8	8	8
9	9	9	9
10	10	10	10
11	11	11	11
12	12	12	12
13	13	13	13
14	14	14	14
15	15	15	15
16	16	16	16
17	17	17	17
18	18	18	18
19	19	19	19
20	20	20	20
21	21	21	21
22	22	22	22
23	23	23	23
24	24	24	24
25	25	25	25
26	26	26	26
27	27	27	27
28	28	28	28
29	29	29	29
30	30	30	30
31	31	31	31
32	32	32	32
33	33	33	33
34	34	34	34
35	35	35	35
36	36	36	36
37	37	37	37
38	38	38	38
39	39	39	39
40	40	40	40
41	41	41	41
42	42	42	42
43	43	43	43
44	44	44	44
45	45	45	45
46	46	46	46
47	47	47	47
48	48	48	48
49	49	49	49
50	50	50	50

8/196/63/000/003/005/012
A152/A126

teknika i energetika

S/196/63/000/003/005/012

A052/A126

... with a widened baked interval

to use as a flux feldspars (3 - 5% and pegmatites 1/2) ...
... ability of the fluid in baking and to widen this way the bak-
... by


... increased the vitreous-phase content

Strength of ...

Card 2/4

baking interval to just over 40 min. ...
12%) and in particular of chalk (4 - 6%) has a positive effect on proper-
ties of steatite. A combined addition of magnosite and chalk gave no posi-
tive results. The widest baking interval (40 min.) maximum density and
 $\rho = 1.550 \text{ kg/cm}^3$ had steatite with 4% bulged chalk and 5% pagmatite. Its
vitreous-phase content to 30%

... of the sieve no. 009 up to 100%



AUTHORS: Ave'nikov, V. G., Zin'ko, E. I., S/072/60/000/03/007/023
Zasodatsleva, N. A. B003/B008

TITLE: High-frequency Ceramics on Wollastonite Basis

PERIODICAL: Steklo i keramika, 1960, Nr 3, pp 25-29 (USSR)

ABSTRACT: Wollastonite has lately been used increasingly for electro-ceramics owing to its favorable electric properties. In the Soviet Union there are larger wollastonite deposits in the following regions: in the region north of the Balkhash Lake, in the "Western Dzhangalyk" Mines in Northern Tadzhikistan, where wollastonite accumulates as barren rock and goes into backfilling, in the Aldan region of the Yakutskaya ASSR; according to information from the Institut geologii AN Uzbekskoy SSR (Institute of Geology of the AS of the Uzbekskaya SSR) in the Nakpay deposit, but also in other deposits of Uzbekistan: Lyangar, Koytash, Ingichka, Chatkal'skiy Range. Wollastonite from Dzhangalyk was investigated. The most important impurities are epidote, diopside and sphene. The material was cleaned twice (Table 2) with the separator 138-SE at the laboratoriya elektricheskikh i magnitnykh metodov obogashcheniya, Institut gornogo dela AN SSSR (Laboratory for Electric and Magnetic Dressing Methods of the Institute of Mining AS USSR); analyses are given in table 3. A ceramic mass

Card 1/2

High-frequency Ceramics on Wollastonite Basis

S/072/60/000/03/007/023
BC03/B008

was produced with an addition of 10% barium carbonate and 20% clay from Chasov Yar; the electric properties were investigated (Fig 1). Since wollastonite changes practically irreversibly into pseudowollastonite, at about 1250° with a change in structure, it was the main thing to lower the firing temperature. Four masses were produced: VD-6 with 5% lead boron glass, VD-7 with 5% ascharite, VD-8 with 10% quartz sand and VD-9 with 3% boracite glass. The investigation with the petrographic microscope was carried out by E. I. Medvedovskaya (Figs 2-4). The firing temperatures are 1120, 1210, 1290, and 1300°. For wollastonite from Dzhangalyk the change into pseudowollastonite occurs at 1290°. There are 4 figures and 5 tables.

Card 2/2

ZASEL, Jan

On the program of schooling drivers. Motor 11 no.42:11 21 0 '62.

ZASEL'SKIY, D. A. and LISHNEVSKAYA, L. A.

Interaction of Diazo-Compounds with Sulfamic Acid and its Derivatives. II. Study of the Properties of Aryl-1-Methyl-3-Triazole Sulfo Acids-3, page 446, Sbornik statey po obshchey khimii (Collection of Papers on General Chemistry), Vol I, Moscow-Leningrad, 1953, pages 762-766.

ZASHELSKIY, D. Z. and LISHNEVSKAYA, L. A.

Interaction of Diazo-Compounds with Sulfamic Acid and its Derivatives. I. Interaction of Diazo-Compounds with N-Methyl Sulfamic Acid, page 434, Sbornik statey po obshchey khimii (Collection of Papers on General Chemistry), Vol I, Moscow-Leningrad, 1953, pages 762-766.

S/032/60/026/008/043/046/XX
B020/B052

AUTHORS: Marayev, S. Ye. and Zaselyan, B. N.

TITLE: News in Brief

PERIODICAL: Zavodskaya laboratoriya, 1960, Vol. 26, No. 8, p. 1029

TEXT: The authors report on a new method of producing boats of pure alumina for the zone melting of aluminum. A mixture of alumina (90-95%) and aluminum powder (5-10%) for radio valves is carefully mixed, an aqueous solution of starch and molasses (2:1) is added and carefully mixed again. Sample rods are then pressed from this mixture. They are sintered for 5-6 hours at 1200°, and cooled down together with the furnace. Holes are then drilled into the rods by a milling machine with welded alloy cogs. The boats are sufficiently strong and endure a considerable number of melts without polluting the aluminum. ✓

ASSOCIATION: Vsesoyuznyy nauchno-issledovatel'skiy alyuminiyevomagniyevyy institut (All-Union Scientific Research Institute of Aluminum and Magnesium)

Card 1/1

1 29157-46 ENP(k)/ENT(m)/I/EWA(d)/ENP(v)/ENP(t)/ETI IJP(S) JD/HM
 ACC NR: AP6018662 SOURCE CODE: UR/0125/66/000/003/0077/0077

AUTHOR: Ushakova, S. Ye.; Zaslavyan, B. H.; Kokoreva, I. I. 62
B
A
 DRG: none
 TITLE: Microscopic investigation of joints made by diffusion welding in a vacuum
 SOURCE: Avtomaticheskaya svarka, no. 3, 1966, 77

TOPIC TAGS: diffusion welding, vacuum welding, copper, steel, electron microscope, welding technology/H2T copper, 30 KhGSA steel, JEM-5Y electron microscope
 ABSTRACT: Vacuum diffusion welding is one of the most promising methods for joining metals. H2T copper, H2T copper with 30KhGSA steel and 30KhGSA steel alone were compared to study methods for investigation of the diffusion layer. The experimental SDVU-0 installation was used for welding. The weld zone of the specimens was first studied on an MIN-8M metallographic microscope (1000x). A JEM-5Y electron microscope was used for a more detailed study. The electron microscope images with a resolution of 0.1 microns for the structure of metals and alloys with a magnification of 100,000x. The electron microscope film replicas were used in the electron microscope studies. The study shows that the quality of a joint made in a vacuum is difficult to determine at small magnifications. For instance, incomplete welding is barely distinguishable at 150-200x, but become clearly visible at 600-800x. It is impossible to find the joint in copper specimens at low magnification, the boundary appears only at

Card 1/2

UDC: 621.791.89:533.5

I 29157-66

ACC NR: AF6018662

600-900X. The diffusion layer is very similar in structure to the grain boundaries in copper. Thus, low magnifications (150-300X) when studying specimens made up of homogeneous materials may result in erroneous conclusions on the quality of the weld. The boundary in specimens welded from two dissimilar materials (30KHGSA steel and M2T copper) is clearly visible to the unaided eye. A dark strip with bulges is visible at low magnifications (150-300X) giving the impression of incomplete welding. Higher magnification reveals that this is a transition layer. The diffusion layer has a structure which differs sharply from that of steel and is similar to the structure of copper although somewhat denser. In two copper specimens, the diffusion layer for the most part is a continuation of the copper grains in one specimen. The diffusion layer is sometimes extremely small, but in most cases it is of considerable size. The diffusion layer of a copper-copper joint is 3 or 4 times as broad as the copper-steel layer, but has a structure similar to that of copper. Extremely high magnifications (50,000X) cannot be used for judging welding results. In this case the transition from the diffusion layer to the base metal is insufficiently sharp. Magnifications from 600-900 to 10,000-15,000 are optimum for determining the quality of vacuum diffusion welding. Orig. art. has: 2 figures. [JPRS]

SUB CODE: 13, 11 / SUBM DATE: none

Card 2/2 AC

SIN'KOV, V.M., kand. tekhn. nauk; ZASENKO, V.L., inzh.; KOVALENKO, V.P.,
inzh., FOL'KMAN, K.Yu., inzh.

Computer for calculating the distribution of active loads with
a given fuel consumption. Elektrichestvo no.8:9-15 Ag '60.
(MIRA 13:8)

1. Institut avtomatiki Gosplana USSR.

(Electronic analog computers)
(Electric power distribution)
(Electric power plants)

SIN'KOV, V.M., kand.tekhn.nauk; ZAKIDAL'SKIY, A.I., inzh.; ZASENKO, V.I.,
inzh.; SITNIKOVA, I.A., inzh.; FOL'KMAN, K.Yu., inzh.; KHOLMSKIY,
D.V., inzh.

Computers for calculating the most favorable distribution of active
loads in composite electric power systems. Avtom.i prib. no.2:
126-138 '61. (MIRA 14:12)
(Electronic analog computers) (Electric power distribution)

D'YAKOV, A.M., inzh.-mekhanik; LEKHIKOYNEEN, M.M.; BRATIL'CHUK, P.L., kand.tekhn.
nauk, red.; ZASENTSEV, I.I., inzn., red.

[Technological process of the overhauling of the GAZ-51,
GAZ-63-63A, GAZ-93, PAZ-651-652 motor vehicles] Tekhno-
logicheskii protsess kapital'nogo remonta avtomobilei
GAZ-51, GAZ-63-63A, GAZ-93, PAZ-651-652; metodicheskoe
posobie. Dushanbe, Tadzhikskii sel'khoz. in-t, 1963. 126 p.
(MIRA 17:9)

ZAWADZKI, Zbigniew A.; TOPOJSKA, Paula; ZASEPA, Ryszard

Hemoglobin, hematocrit & erythrocyte count in blood donors. Polski tygod. lek. 13 no.50:2010-2016 15 Dec 58.


1. Z Kliniki Hematologicznej; kier. prof. dr med. W. Iwkwicz. Instytut Hematologii; dyr. doc. dr med. A. Trojanowski oraz ze wszystkich cojewódzkich stacji krwiodawstwa. Adres: Warszawa 10, Krucza 51 m. 7.

(BLOOD TRANSFUSION

erythrocyte count, hematocrit & hemoglobin values in donors (Pol))

(ERYTHROCYTES

count, hematocrit & hemoglobin values in blood donors (Pol))



ZASEPA, Wojciech

Preparation and characteristic of silver hydrosol. *Mat chemia*
4:55-64 '61.

1. Katedra Chemii Fizycznej, Poznan.

ZASEPA, Wojciech

Photovoltaic properties of silver hydrosol. Mat chemia 4:65-72 '61.

1. Katedra Chemii Fizycznej, Poznan,

ZASEPA, W.

Mistr: 4E2c(j)

15

4
2-may

~~/Becquerel effect in some xantheno dyes and in aqueous
 solutions of their copper salts. Stefan Paszye and Wojciech
 Zasepa (Univ. Poznan, Poland). *Polska Akad. Nauk, Prace
 Nauk. Wzrost. Mat. Przyrod.*, Prace Komisji Mat.
 Przyrod. 7, No. 8, 13-26 (1958) (English summary).—
 Becquerel effect of eosin, erythrosin, Bengal rose, and ura-
 nin and of their Cu⁺⁺ salts suspended in water was exam-
 ined with a Pt smooth electrode or Cu gauze electrode. Photo-
 sensitivity of salts was slight. Electrode potentials decreased
 with time in dark and a little faster in light. The system
 Cu⁺⁺/aq dye salt showed notable photosensitivity. elec-
 trode potential was increased by irradiation and dropped
 rapidly after interruption of irradiation. J. Stecki.~~

74
41

2-9

ZASEPA, Wojciech

Method of obtaining and characteristics of silver hydrosol. Mat
chemia 4:55-64 '61.

1. Uniwersytet im. Adama Mickiewicza w Poznaniu, Katedra Chemii
Fizycznej.

ZASEPA, Wojciech

Photovoltaic properties of silver hydrosol. *Mat chemia* 4:65-72 '61.

1. Uniwersytet im. Adama Mickiewicza w Poznaniu, Katedra Chemii Fizycznej.

ZASETSKAYA, G.I., mladshiy nauchnyy sotrudnik

Use of new trimming materials in the manufacture of fur hats.

Kozh.-obuv.prom. 4 no.11:12-13 N '62.

(MIRA 15:11)

(Hats)

BERG, P.P.; FEYGEV'SON, B.Yu.; Primali uchastiye: ~~EASETSKIY~~, G.F., inzh.;
RAKOGON, V.G., inzh.; KUZNETSOV, Ye.I., inzh.; SZOSYFLEVA, A.N.,
starshiy tekhnik; USTICHENKO, R.D., starshiy tekhnik.

Metal shell molds. Lit. proizv. no.10:32-53 0 '60. (MIRA 13:10)
(Foundaries--Equipment and supplies)

GUGLIN, N.H.; PROVORNYI, A.K.; ZASETSKIY, G.F.; GULYAYEV, B.B.

Manufacture of shaped steel ingots by continuous casting.

Steel 21 no.10:895-899 0 '61.

(MIRA 14:10)

(Continuous casting)

(Steel ingots)

S/133/60/000/011/018/023
A054/A029

AUTHORS: Verbol'skaya, Ye.D., Zaslavskiy, G.F., Isakov, I.V., Engineers,
Khlebnikov, A.Ye., Doctor of Technical Sciences

TITLE: Experience in the Treatment of Molten Steel With Rare-Earth
Metals

PERIODICAL: Stal', 1960, No. 11, pp. 1030-1033


TEXT: In order to obtain more information on the possibilities of improving the plastic properties of chrome-nickel-molybdenum alloys by the addition of rare-earth metals, tests were carried out (with the cooperation of Z.B. Vagonov and V.I. Belyayev) by treating these alloys with a mixed metal containing 40-50% cerium, 15-20% lanthanum, 10-20% other rare-earth metals and 5-10% iron. The test steel was melted in an induction vacuum furnace with a magnesite crucible of 150 kg capacity, the charge consisted of armco steel and synthetic iron, the melting temperature was 1,550-1,580°C; the alloying elements were added without affecting the vacuum after a certain interval for the degasification of the metal. Pouring took place in an argon atmosphere at a pressure of 600-700 mm Hg, the test ingots were 140 x 140 mm and weighed about 70 kg. Investigations to determine the influence of the rare-earth metal additives on the sulfur content and on the quantity of non-
Card 1/3

S/133/60/000/011/018/023
A054/A029

Experience in the Treatment of Molten Steel With Rare-Earth Metals

metallic inclusions revealed that under the effect of rare earth elements the non-metallic phase still forms in the liquid steel before the precrystallization period. The composite inclusions which are formed during this period coagulate easily and float on the surface of the casting. During this floating period these inclusions can be captured in the crust zone of the casting by the growing crystals. The total amount of sulfur in these agglomerations is about 0.18-0.19%, while the liquid steel before treatment with mixed metal contains about 0.024-0.030% S and the finished metal about 0.003-0.016% S. The sulfur residue in the metal decreases in proportion with the increase in the quantity of the mixed metal added, and the longer the metal is kept liquid, the larger is the amount of sulfur inclusions which can be removed from the casting. The quantity of oxide-inclusions also decreases in the rare-earth metal alloyed steels, irrespective of the melting method; only the amount of aluminates increases to some extent. The tests carried out to determine the mechanical properties of the new type steel showed that rare-earth metal alloyed steels of the same composition but cast in open and in vacuum furnaces had practically the same values as regards strength and tenacity, in cast and in

Card 2/3



S/133/60/000/011/018/023
A054/A029

Experience in the Treatment of Molten Steel With Rare-Earth Metals

rolled condition as well; the steel melted in a conventional furnace has a tenacity 1.5-2.0 times higher than the same type of steel deoxidized by 0.07% Al; when melted in a vacuum furnace, the increase in tenacity is 2-2.5 times greater compared with the Al-treated steels; the steel with a C-content of 0.40% shows the same plastic properties in melted and in rolled condition as the chrome-nickel-molybdenum steels containing 0.30%C and produced in open-hearth furnaces according to the direct reduction process. In the rolled steels containing 0.40% C and alloyed with rare-earth metals no anisotropy in the mechanical properties can be observed at tempering, both as regards the sorbite and the martensite structure. The laboratory tests were confirmed by industrial scale tests in the UZTM. The samples taken from various (upper and lower) parts of the sheets rolled from the test ingots (with a C content of 0.41% containing chrome-nickel-molybdenum deoxidized in the ladle by 350 g/t Al and containing 2 kg/t mixed metal) displayed remarkable chemical homogeneity. Practically no segregation of carbon, sulfur and phosphorus could be observed. From the tests it is assumed that rare-earth metal alloyed chrome-nickel-molybdenum steels can be used in machinery constructions for replacing rolled or hammered machinery parts. There are 2 figures, 6 tables and 3 Soviet references.

Card 3/3

SOV/128-59-3-12/31

18(5)

AUTHOR: Smolenskiy, S.I., Guglin, N.N., ~~Vassilakiy, G.P.~~
Provornyy, A.K. and Tyutev, V.A., Engineers

TITLE: Steel Molds for Large Steel Castings

PERIODICAL: Liteynoye Proizvodstvo, 1959, Nr 3, pp 23-26 (USSR)

ABSTRACT: Metal dies for casting of large steel cast shapes are made from steel or cast iron. As demonstrated by the experiments the cast iron dies are unserviceable within short periods. Against that steel dies show far better properties. A method has been worked out to pour large shell-type castings of several tons of weight by means of the permanent die method. Special designs had to be built for this method. Pouring of the metal is done in five steps and in accordance with the design of the casting and in accordance with the technology of the die shape. The experimental method showed that within a certain time interval all types of the die designs are distorted and that hair line cracks appear on the wor-

Card 1/3

SOV/128-59-3-12/31

Steel Molds for Large Steel Castings

king surface. Consequently the quality of the experimental dies is judged by way of two characteristics:

- a) According to the number of pourings possible till to the point of repair, when the cracks have to be eliminated;
- b) To the point when the exact dimensions are lost and must be re-machined.

Several tests have been made to study the properties of the metal dies, to establish the suitable shapes and the necessary thickness of the walls. By means of tables, and photographs the results of the tests in connection with the contents of sulphur, of carbon, and in connection with the mean thickness of the walls and the point of formation of hair line cracks are published. Conclusion: Best results will be achieved with metal dies having a wall thickness of 150 to 170 mm. The steel used for the die should not have more than 0,10% carbon and not more than 0,025% of sulphur

Card 2/3

Steel Molds for Large Steel Castings

SOV/128-59-3-12/31

Permanent Metal Dies from Steel for the Casting of Large Steel
Casting Shapes

contents. There are 7 graphs and 2 photographs.

Card 3/3

GUREVICH, S.M.; DIDKOVSKIY, V.P.; NOVIKOV, Yu.K.; FILORIK'YAN, B.K. (Moskva);
ZASETSKIY, G.F. (Moskva); KRAVCHENKO, V.F. (Moskva); NOVIKOVA, A.A. (Moskva)

Properties of commercial titanium and alloys of the OT4-type prepared
by electric slag melting. Avtom. svar. 16 no.4:27-33 Ap '63.
(MIRA 16:4)

1. Institut elektrosvariki im. Ye.O.Patona An UkrSSR (for Gurevich,
Didkovskiy, Novikov).
(Titanium—Electrometallurgy) (Zone melting)

ZASETSKIY, G. F.

VERBOL'NAYA, Ye. D.; ZASETSKIY, G. F.; IBRAKOV, I. V.; KHEBENKOV, A. Ye.

Vliyaniye sposobov raskisleniya na svoystva khromo-nikel'-molibdenovoy stali.

report submitted for the 5th Physical Chemical Conference on Steel Production, Moscow, 30 Jun 1959.

ZASETSKIY, G.F.

115

PHASE I BOOK EXPLOITATION SOV/5411

Konferentsiya po fiziko-khimicheskim osnovam proizvodstva stali. 5th,
Moscow, 1950.

Fiziko-khimicheskiye osnovy proizvodstva stali; trudy konferentsii
(Physicochemical Bases of Steel Making; Transactions of the
Fifth Conference on the Physicochemical Bases of Steelmaking)
Moscow, Metallurgizdat, 1961. 512 p. Errata slip inserted.
3,700 copies printed.

Sponsoring Agency: Akademiya nauk SSSR. Institut metallurgii imeni
A. A. Baykova.

Responsible Ed.: A. M. Samarin, Corresponding Member, Academy
of Sciences USSR; Ed. of Publishing House: Ya. D. Rozentsveyg.
Tech. Ed.: V. V. Mikhaylova.

Card 1/18

115

Physicochemical Bases of (Cont.)

SOV/5411

PURPOSE: This collection of articles is intended for engineers and technicians of metallurgical and machine-building plants, senior students of schools of higher education, staff members of design bureaus and planning institutes, and scientific research workers.

COVERAGE: The collection contains reports presented at the fifth annual convention devoted to the review of the physicochemical bases of the steelmaking process. These reports deal with problems of the mechanism and kinetics of reactions taking place in the molten metal in steelmaking furnaces. The following are also discussed: problems involved in the production of alloyed steel, the structure of the ingot, the mechanism of solidification, and the converter steelmaking process. The articles contain conclusions drawn from the results of experimental studies, and are accompanied by references of which most are Soviet.

Card 2/18

Physicochemical Bases of (Cont.)

SOV/5411

(Zlatoust Metallurgical Plant) A. K. Petrov, Engineer, O. M. Chekhomov, G. A. Khasin, A. I. Markelov, I. S. Kutuyev, R. I. Kolyasnikova, and Ye. D. Mokhir].

Paton, B. Ye., B. I. Medovar, Yu. V. Latash, B. I. Maksimovich, and A. F. Tregubenko. Electroslag Remelting of Alloyed Steels and Alloys as an Effective Means for Improving Their Quality

3
3
118

Verbol'skaya, Ye. D., G. F. Zasetkiy, I. V. Isakov, and A. Ye. Khlebnikov. Various Methods of Treating Molten Chromium-Nickel-Molybdenum Steel and Their Effect on Its Properties

127

Yedneral, F. P. Application of Complex Deoxidizers for the Purpose of Shortening the Reduction Period of Electromelting of Constructional Steels

137

Yedneral, F. P. The Change in the Bath Composition of an Electric-

Card 7/18

18(5,7)
AUTHORS:

SOV/128-59-4-15/27
Zasetskiy, G.F., and Snakhnovich, V.A., Engineers

TITLE:

New Method to Study Solidification Processes

PERIODICAL:

Liteynoye Proizvodstvo, 1959, Nr 4, pp 34-35 (USSR)

ABSTRACT:

Under the methods to determine the peculiarities in the formation of the hard phase during the solidification process of castings, the authors special interest is directed to one method which is based on the introduction of radioactive isotopes into the fluid phase and their distribution in between the fluid and the hard phase. This method makes it possible to determine at any given moment the extent of the hard phase. It is also possible to trace a heterogeneous concentration. Although this method is not questioned in its value, it is applied only to a small extent as a result of the high costs connected with it. It was therefore decided (on a proposal of G.F. Zasetskiy) to introduce sulphur into the fluid phase in order to get a better knowledge of the solidification process. This method is based on the difference in the

Card 1/3

New Method to Study Solidification Processes SOV/128-59-4-15/27

diffusion of sulphur in the fluid and in the hard phase, and also on the fact, that crystal sulphur combines with iron. The amount of sulphur in the iron indicates at any given moment from the beginning of the solidification, how thick the layer of the hard phase is. The amount of sulphur brought into the fluid phase should exceed the normal percentage of sulphur in the metal by 5 to 10 times. To bring the sulphur in the fluid phase of the casting it is necessary to keep the riser part of the casting in a fluid state. This is done by heating the casting. This method makes it possible to trace the development of the different stages in the solidification process. Furthermore the separating surface of the fluid and the hard phase, the dendrite structure on this surface, the metal flow in the fluid phase, and the influence of that flow on the formation of the microstructure of the cast can be determined. Figure 1 shows the outline of the layer in the hard phase, figure 2 shows

Card 2/3

New Method to Study Solidification Processes. SOV/128-59-4-15/27

traces of sulphur. The mathematical results will be described in a forthcoming paper. There are 2 photographs.

Card 3/3

VERBOL'SKAYA, Ye.D., inzh.; ZASETSKIY, G.F., inzh.; ISAKOV, I.V., inzh.;
KHLEBNIKOV, A.Ye., doktor techn.nauk

Treatment of molten steel by rare earth elements. Stal' 20 no.11:1030-
1033 N '60. (MIRA 13:10)
(Steel--Metallurgy) (Rare earth metals)

ZASITSKIY, V.

19049

USSR/Automobile Plants 4403.0500, 5405. Feb 1948

"Cost Accounting in Shops, Sections and Workers' Brigades," V. Zasetkiy, 4 pp

"V Pomeshch' FZMK" Vol IX, No 4

Profitable effects of cost accounting illustrated in specific workshops, sections and brigades of Moscow Automobile Plant imeni Stalin, Gor'kiy Automobile Plant imeni Molotov, Uralmash, Ural Aluminum Plant, and Second Moscow Clock Plant.

II

19049

ZASHCHBLKIN, V., kapitan dal'nego plaveniya

Don't needlessly encumber supplementary navigational calculations.
Mor.flot 19 no.6:45 Je '59. (MIRA 12:9)

1. Parokhod "Derzhavin" Murmanskogo parokhodstva.
(Navigation)

35422. Primenenie betona v dorozhnom stroitel'stve. Trudy IV Vsesoyuz. Konf-tsa
Po Betonu i Zhelezobetonu. Konstruktsiyam. Ch. 7. M.-L., 1949, S. 121-26

SO: Letopis' Zhurnal'nykh Statey Vol. 34, Moskva, 1949

SHNESTOPNIKOV, S.V., kandidat tekhnicheskikh nauk; IVANOV, F.M., kandidat tekhnicheskikh nauk; ZASHCHEPIN, A.N., kandidat tekhnicheskikh nauk; LYUBIMOVA, T.Yu., kandidat khimicheskikh nauk; GRADISECHEV, N.Ye., redaktor; KOVALIKHINA, N.F., tekhnicheskiy redaktor

[Concrete with plasticiser agents] TSementnyi beton s plastifi-
tsiruiushchimi dobavkami. Moskva, Izd-vo dorozhno-tekhn.lit-ry
Gushodora MVD SSSR, 1952. 105 p. [Microfilm] (MIRA 9:3)
(Concrete)

ZASHCHEPIN, A.N.; ZELENOV, K.T., redaktor.

[Technical rules for the construction of cement and concrete coatings] Tekhnicheskie pravila ustroistva tsementobetonnykh pokrytii. Uтверждено 26 dek. 1952 g. [Sostavleny A.N.Zashchepinym, dopolnemy i otrektirovany K.T.Zelenovym] Moskva, Izd-vo dorozhno-tekhn. lit-ry, 1952. 115 p. (MLRA 7:6)

1. Russia (1923- U.S.S.R.) Glavnoye upravleniye shosseynykh dorog.
(Roads, Concrete)

ZASHCHEPIN, A.N., kandidat tekhnicheskikh nauk; ZEL'MANOVICH, M.S.,
kandidat tekhnicheskikh nauk; LUK'YANOV, N.K., inzhener.

[Over-all mechanization of concrete road construction] Kompleksnaia
mekhanizatsiia stroitel'stva tsementobetonnykh pokrytii. Moskva,
Izd-vo dorozhno-tekhn.lit-ry, 1953. 91 p. (MIRA 7:2)
(Roads, Concrete)